

Sensys 110° thin door hinge without self closing feature

- ▶ Fast assembly hinge without Silent System for thin doors



product
design
award

2009 ■



reddot design award
winner 2008

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8676. Opening angle 110° Without self closing feature for Push to Open applications. For door thicknesses from 10 mm to 16 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Overlay door
- Half overlay
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Push to open assisted opening



Further information: www.hettich.com

Sensys 110° standard hinge without self closing feature

▶ Fast assembly hinge without Silent System



product
design
award

2009 ■



reddot design award
winner 2008

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8675. Opening angle 110° Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 24 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Overlay door
- Half overlay
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Opening angle limiter
- ▶ Push to open assisted opening



Further information: www.hettich.com

Sensys 165° zero protrusion hinge without self closing feature

▶ Wide angle fast assembly hinge without Silent System



reddot award 2014
winner

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8687. Opening angle 165°. Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 32 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Overlay door
- Half overlay

Types:

- different drilling patterns
- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Opening angle limiter
- ▶ Soft opening
- ▶ Push to open assisted opening



Further information: www.hettich.com

Sensys 95° thick door hinge without self closing feature

- ▶ Fast assembly hinge without Silent System for thick doors



reddot design award
winner 2008



product
design award
2014

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8661. 95° opening angle. Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 32 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Overlay door
- Half overlay
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Opening angle limiter
- ▶ Push to open assisted opening



Further information: www.hettich.com

Sensys 95° angle hinge W30 without self closing feature

- ▶ Fast assembly hinge without Silent System for 30° face angle application



product
design
award

2009 ■



reddot design award
winner 2008

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8669 for 30° face angle applications. 95° opening angle. Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 28 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Overlay door
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Opening angle limiter
- ▶ Push to open assisted opening



Further information: www.hettich.com

Sensys 95° angle hinge W45 without self closing feature

- ▶ Fast assembly hinge without Silent System for 45° face angle application



product
design
award

2009 ■



reddot design award
winner 2008

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8669 for 45° face angle applications. 95° opening angle. Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 28 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Overlay door
- Inset door

Types:

- different drilling patterns

- different fastening methods


Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Opening angle limiter
- ▶ Push to open assisted opening



Further information: www.hettich.com

Sensys 95° angle hinge W90 without self closing feature

- ▶ Fast assembly hinge without Silent System for 90° face angle application



product
design
award

2009 ■



reddot design award
winner 2008

- ▶ Award winning, perfectly balanced design
- ▶ Operational reliability over a temperature range of +5°C to +40°C
- ▶ Cost efficiency from the ability to save additional hinges on specific door formats

Specification

Sensys fast assembly hinge from Hettich. 8669 for 90° face angle applications. 95° opening angle. Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 28 mm. Defined versions also available in obsidian black.

Door mounting options for:

- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 1 mm / - 2 mm. Integrated depth adjustment + 3 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm and the cup
- ▶ Opening angle limiter
- ▶ Push to open assisted opening



Further information: www.hettich.com